



**MAMMUT
WORLD**

تریلر تیغه تانکر سه محور
Tank Carrier Semi - Trailer 3 Axles



PROTECTED BY
ELECTRODEPOSITION COATING
○○○=○ **ED**

EXPERIENCE THE BEST

Tank Carrier Semi - Trailer 3 Axles

Dimensions	Length: 11,100 mm / Width: 2,550 mm / Height: 1,340 mm
Max. Payload	28,000 kg
Weight	3,750 Kg- Approximately
Chassis	Chassis & components from St 52-3 / QST 380 / S 500 / Automatic CO2 welding technology / Merkle, Germany / Main I beams with standard flat bar / All steel stamping parts are assembled using special fixture
Axle	3 x 9 tons SAF® / BPW® / MAMMUT® Front axle with automatic lifting capability
Suspension	Air suspension with special shock absorbers / Lowering and rising of trailer height
Tire/Rim	6 x Radial tires 385/65 R22.5 / 6 x Single rims 11.75xR22.5 ^f
Landing Gear	2 mechanically operated landing legs 24 tons dynamic capacity & 50 tons static capacity / Operated from right side.
King Pin	2" dia. (162 KN) with coupling according to SAE standard with special bolster plate according to UNECE regulation ECE-R55 standard / Corner dimension: 2040 mm
Braking System	Knorr ,WABCO 2S/2M, Disk / according to ECE-R13 standard. Dual circuit pneumatic with automatic load sensing valves / Two double acting diaphragm brake chambers (2 rear axles) / EBS incl. ABS & RSP (Roll Stability Program) / Emergency valve / Parking brake/Reset-to-Ride height function.
Electrical System	7 & 15 Poles quick release connector with 24 volts rear and side lights plus LED alarming system / According to UNECE regulation R48
Painting	Shot blast preparation process (according to SA2.5 standard) and with cationic phosphate; ED with a thickness of 20 microns and a powder color of 80 microns or polyurethane with a thickness of 100 microns; with color rally according to customer
Accessories	Rear guard protection / Rear under-run protection according to UNECE Regulation ECE-R73 / 6 x Semi-circle mud guards / 2 x Rear Spray suppression system according to UNECE Regulation-EU109/2011 / 2 x Wheel chocks with holders / Spare wheel carrier with clamp mechanism / 1 x Tool box (1 m) / Side protection and Reflective outline marking according to UNECE Regulation
Options	125 L Stainless steel water tank / Spare tire & rim / Tire-pressure monitoring system (TPMS)

تریلر تیغه تانکر سه محور

ابعاد	طول (میلیمتر): ۱۱,۱۰۰ / عرض (میلیمتر): ۲,۵۵۰ / ارتفاع (میلیمتر): ۱,۳۴۰
ظرفیت	۲۸,۰۰۰ کیلوگرم
وزن	۳,۷۵۰ کیلوگرم - تقریبی
شاسی	شاسی و قطعات از فولاد با استحکام بالا St 52-3/ QST 380 / S 500 / جوش آرگون اتوماتیک با فن آوری مرکله آلمان / تیرهای اصلی با تسمه استاندارد / مقاطع پرسی فولادی مونتاژ شده در فیکسچر مخصوص
محور	سه عدد محور ۹ تن SAF® / BPW® / MAMMUT® محور جلو دارای بالابر اتوماتیک با بوستر تک
زیربندی	سیستم تعلیق بادی بالنی و کمک فنر مخصوص / قابلیت تنظیم ارتفاع تریلر
رینگ و لاستیک	شش حلقه لاستیک سایز 385/65/ R22.5 / شش عدد رینگ یک تکه سایز 11.75xR22.5 ^f
پایه توقف	دو سرعت با ظرفیت دینامیکی ۲۴ تن و ظرفیت استاتیکی ۵۰ تن / سمت کمک راننده
میل ریش	۲ اینچ با قدرت ۱۶۲ کیلونیوتن به همراه فلنج مربوطه مطابق استاندارد SAE با ضخامت صفحه ریش مخصوص شعاع چرخش ۲۰۴۰ میلی متر
سیستم ترمز	دیسکی Knorr 2S/2M , WABCO بر طبق استاندارد ECE-R13 / دو مسیر باد اصلی برای تمام چرخها همراه شیر سبک و سنگین اتوماتیک بار / ۲ عدد بوستر جفت برای دو محور عقب / سیستم EBS (ترمز ضد قفل و سامانه ضدواژگونی RSP) / ترمز اضطراری / سیستم قفل پارک / سیستم تنظیم خودکار ارتفاع
سیستم برق	دارای کلید ۷ و ۱۵ پل با خط برق ۲۴ ولت چراغهای عقب و بغل / سیستم هشدار از نوع LED خارجی طبق استاندارد جهانی R48
رنگ شاسی	فرآیند آماده سازی به روش شات بلاست (مطابق استاندارد SA2.5) و دارای فسفات تری کاتیونیک ; ED با ضخامت حدودی ۲۰ میکرون و رنگ پودری با ضخامت حدود ۸۰ میکرون و یا پلی اورتان با ضخامت حدودی ۱۰۰ میکرون ; با رال رنگ طبق نظر مشتری
متعلقات	سپر عقب / سپر محافظ عقب بر طبق استاندارد جهانی ECE-R73 / ۶ عدد گلگیر نیم دایره / ۲ عدد گل پخش کن عقب با شلگیر بر طبق استاندارد جهانی EU109/2011 / ۲ عدد دنده پنج و نگهدارنده / زاپاس بند مستحکم کلمپی / یک عدد جعبه ابزار ۱ متری / گارد بغل / شبرنگ مخصوص نصب شده عقب بر طبق استاندارد جهانی
قابل سفارش	تانک آب استیل ۱۲۵ لیتری / رینگ و لاستیک زاپاس / سیستم نشان گر باد تایر

Certified by INSO (Iran National Standards Organization) & Type approval of vehicles - European Commission

دارای مجوزات تایید نوع و شماره گذاری از سازمان ملی استاندارد ایران و کنوانسیون اروپا

Certificate Control Quality & Testing

۰۲۶ ۴۵۰۰

info@mammutworld.com

mammut world group

www.mammutworld.com

mammutworld

اتوبان کرج قزوین ۵ کیلو متر بعد از پل هوایی کردان شهرک صنعتی ماموت

